


















Dahua HDCVI Camera & DVR Price List November - 2021






| SL | Model | Product | Product Specification | Price |
|----|------------------------------------|---|--|----------|
| 01 | DH-HAC-T1A21P |  | 2MP HDCVI IR Dome Camera > Max. 30fps@1080P > 2.8 mm fixed lens > Angle of View 103 Degree > Max. IR length 20m, Smart IR > Casing: Plastic | 1,325.00 |
| 02 | DH-HAC-B1A21P |  | 2MP HDCVI IR Bullet Camera > Max. 30fps@1080P > 3.6 mm fixed lens > Angle of View 93 Degree > Max. IR length 20m, Smart IR > Casing: Plastic | 1,400.00 |
| 03 | DH-HAC-HDW1200RP |  | 2MP HDCVI IR Dome Camera > Max. 30fps@1080P > 2.8 mm fixed lens > Angle of View: 101 Degree > Max. IR length 20m, Smart IR > Casing: Plastic | 1,425.00 |
| 04 | DH-HAC-HFW1200RP |  | 2MP HDCVI IR Bullet Camera > Max. 30fps@1080P > 3.6 mm fixed lens > Angle of View 84 Degree > Max. IR length 20m, Smart IR > Casing: Plastic | 1,500.00 |
| 05 | DH-HAC-T2A21P (Full Metal Body) |  | 2MP HDCVI IR Dome Camera > Max. 30fps@1080P > 2.8 mm fixed lens > Angle of View 103 Degree > Max. IR length 20m, Smart IR > Casing: Metal | 1,550.00 |
| 06 | DH-HAC-B2A21P (Full Metal Body) |  | 2MP HDCVI IR Bullet Camera > Max. 30fps@1080P > 3.6 mm fixed lens > Angle of View 93 Degree > Max. IR length 20m, Smart IR > Casing: Metal | 1,575.00 |
| 07 | DH-HAC-HFW1200TLP |  | 2MP HDCVI IR Bullet Camera > Max. 30fps@1080P > 3.6 mm fixed lens > Angle of View 84 Degree > Max. IR length 40m, Smart IR > Casing: Metal + Plastic | 1,900.00 |
| | | | | |




| | | | | |
|----|---|---|--|----------|
| 08 | DH-HAC-HDW1200TLP-A (Build in Audio) |  | 2MP HDCVI IR Dome Camera (Build in Audio) <ul style="list-style-type: none"> > Max 30fps@1080P > Built-in mic (-A) > 2.8 mm fixed lens > Angle of View 103 Degree > Max. IR length 30m, Smart IR > Casing Metal | 1,900.00 |
| 09 | DH-HAC-HDW1200EMP |  | 2MP HDCVI IR Dome Camera <ul style="list-style-type: none"> > Max 30fps@1080P > 2.8 mm fixed lens > Angle of View: 101 Degree > Max. IR length 50m, Smart IR > Casing Metal and IP67 | 2,200.00 |
| 10 | DH-HAC-HDW1200EMP-A (Build in Audio) |  | 2MP HDCVI IR Dome Camera (Build In Audio) <ul style="list-style-type: none"> > Max 30fps@1080P > 2.8 mm fixed lens > Built-in mic (Audio) > Angle of View: 101 Degree > Max. IR length 50m, Smart IR > Casing Metal and IP67 | 2,400.00 |
| 11 | DH-HAC-HFW1200SP |  | 2MP HDCVI IR Bullet Camera <ul style="list-style-type: none"> > Max. 30fps@2MP > Max. IR length 30m, Smart IR > 3.6 mm fixed lens > Angle of View 89.9 Degree > Casing Metal | 2,100.00 |
| 12 | DH-HAC-HFW1200TP-A (Built In Audio) |  | 2MP HDCVI IR Bullet Camera <ul style="list-style-type: none"> > Max. 30fps@2MP > Max. IR length 30m, Smart IR > Built-in mic (Audio) > 3.6 mm fixed lens > Angle of View 87.5 Degree > Casing Metal | 2,000.00 |
| 13 | DH-HAC-HDW1209TLQP- LED (Full-color) |  | 2M Full-color HDCVI Dome Camera <ul style="list-style-type: none"> > Full-color > 20m LED distance > Max. 30fps@1080P > 2.8 mm fixed lens > Angle of View 106 Degree > Casing Metal and IP67 | 1,950.00 |



| | | | | |
|----|--|---|---|----------|
| 14 | DH-HAC-HFW1209CP-LED (Full-color) |  Full-color | 2M Full-color HDCVI Bullet Camera > Full-color > 20m LED distance > Max. 30fps@1080P > 2.8 mm fixed lens > Angle of View 106 Degree > Casing Metal + Plastic and IP67 | 1,950.00 |
| 15 | DH-HAC-HDW1209TLQP- A-LED (Full-color with Audio) |  Full-color | 2M Full-color HDCVI Dome Camera > Full-color > 20m LED distance > Max. 30fps@1080P > 2.8mm fixed lens > Angle of View 106 Degree > Built-in mic (Audio) > Casing Metal and IP67 | 2,050.00 |
| 16 | DH-HAC-HFW1209CP-A- LED (Full-color with Audio) |  Full-color | 2M Full-color HDCVI Bullet Camera (Build In Audio) > Full-color > 20m LED distance > Max. 30fps@1080P, > 2.8 mm fixed lens > Angle of View 106 Degree > Built-in mic (Audio) > Casing Metal + Plastic and IP67 | 2,050.00 |
| 17 | DH-HAC-HDW1239TP-A- LED (Full-color Starlight & Build in Audio) |  Full-color | 2M Full-color Starlight HDCVI Dome Camera > Full-color starlight > 40m LED distance > Max. 30fps@1080P > CVI/CVBS/AHD/TVI switchable > Built-in mic(-A), > 3.6mm fixed lens (2.8mm Optional) > Angle of View 106 Degree > Casing Metal and IP67 | 3,050.00 |
| 18 | DH-HAC-HFW1239TLMP- A-LED (Full-color Starlight & Build in Audio) |  Full-color | 2M Full-color Starlight HDCVI Bullet Camera with Audio > Full-color starlight > 40m LED distance > Max. 30fps@1080P > CVI/CVBS/AHD/TVI Switchable > Built-in mic, > 3.6mm fixed lens, > Angle of View 103.6 Degree > Casing Metal + Plastic and IP67 | 3,050.00 |




| | | | | |
|----|--|--|--|----------|
| 19 | DH-HAC-HFW1239MHP- A-LED (Full-color with Audio) |   | 2MP Full-color HDCVI Bullet Camera > 24/7 color imaging, Max. 30 fps@1080p > 50 m illumination distance > Super Adapt, 130 dB true WDR, 3D NR > Built-in mic > 3.6 mm fixed lens > Field of View: H: 86°; V: 46°; D: 101° > CVI/CVBS/AHD/TVI switchable > IP67, DC 12 V | 4,000.00 |
| 20 | DH-HAC-HDW1509TLQ- A-LED (Full-color with Audio) |   | 5MP Full-color HDCVI Quick-to-install Eyeball Camera > Max 25 fps@5MP (16:9 video output) > 120dB true WDR, 3D NR > 24/7 color imaging > 20 m illumination distance > CVI/CVBS/AHD/TVI switchable > Built-in mic (-A), > 3.6 mm fixed lens > Field of View: H: 88; V: 46°; D: 104° > IP67, 12 V DC | 3,800.00 |
| 21 | DH-HAC-HFW1509TLMP- A-LED (Full-color with Audio) |   | 5MP Full-color HDCVI Bullet Camera > Max 25 fps@5MP (16:9 video output) > 120 dB true WDR, 3D NR > 24/7 color imaging > 40 m illumination distance > CVI/CVBS/AHD/TVI switchable > Built-in mic (-A) > 3.6 mm fixed lens >Field of View: H: 88; V: 46°; D: 104° > IP67, 12 V DC | 3,800.00 |



| | | | | |
|----|---|--|---|----------|
| 22 | DH-HAC-HFW1509MHP- A-LED (Full-color with Audio) |   | 5MP Full-color HDCVI Bullet Camera > Max 25 fps@5MP (16:9 video output) > 120 dB true WDR, 3D NR > 24/7 color imaging > 50 m illumination distance > CVI/CVBS/AHD/TVI switchable > Built-in mic > 3.6 mm fixed lens > Field of View: H: 88; V: 46°; D: 104° > IP67, 12 V DC | 5,500.00 |
| 23 | DH-HAC-HFW1200DP |  | 2MP HDCVI IR Bullet Camera > Max. 30fps@2MP > Max. IR length 80m, Smart IR > 3.6 mm fixed lens > Angle of View 84 Degree > Casing Metal | 2,700.00 |
| 24 | DH-HAC-HFW1400THP-I8 |  | 4MP HDCVI IR Bullet Camera > Max. 30fps@4MP > Max. IR length 80m, Smart IR > 3.6 mm fixed lens > Angle of View 87 Degree > Casing Metal + Plastic | 2,700.00 |
| 25 | HD-HAC-HFW1400DP |  | 4MP HDCVI IR Bullet Camera > Max. 30fps@4MP > Max. IR length 80m, Smart IR > 3.6 mm fixed lens > Angle of View 84 Degree > Casing Metal | 3,200.00 |
| 26 | DH-HAC-T1A51P |  | 5MP HDCVI IR Dome Camera > Max. 25 fps@5MP (16:9 video output) > 2.8 mm fixed lens > Max. IR length 20 m, Smart IR > Angle of View (2.8 mm: D: 125° × H: 106° × V 56°) > Max. IR length 20 m, Smart IR > Casing: Plastic | 2,300.00 |



| | | | | |
|----|----------------------|---|---|-----------|
| 27 | DH-HAC-B1A51P |  | <p>5MP HDCVI IR Bullet Camera</p> <ul style="list-style-type: none"> > Max. 25 fps@5MP (16:9 video output) > 3.6 mm fixed lens > Max. IR length 20 m, Smart IR > Angle of View (3.6 mm) D: 104° × H: 88° × V: 46° > Max. IR length 20m, Smart IR > IP67, DC12V > Casing: Plastic | 2,300.00 |
| 28 | DH-HAC-HFW2401TP-Z-A |  | <p>4MP Starlight HDCVI IR Bullet Camera Series 80m</p> <ul style="list-style-type: none"> > Starlight, 120dB true WDR, 3DNR > Max. 30fps@4MP > Audio in interface, built-in mic > 2.7-13.5mm motorized lens > Max. IR length 80m, Smart IR | 7,500.00 |
| 29 | DH-SD49225-HC-LA |  | <p>2MP 25x Starlight IR PTZ HDCVI Camera</p> <ul style="list-style-type: none"> > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 25x optical zoom > Starlight Technology > 120dB true WDR, 3D DNR > Max. 25fps@1080P > IR distance up to 100m | 20,500.00 |
| 30 | DH-HAC-EW2501P |  | <p>5MP HDCVI IR-Fisheye Camera</p> <ul style="list-style-type: none"> > 1/2.8" 5Megapixel progressive scan CMOS > Panoramic fisheye lens > Max. 20fps@5MP > Built-in Mic > 120db true WDR, Starlight, 2D&3D NR > Max. IR length 10m, Smart IR > DC12V | 7,500.00 |
| 01 | XVR1A04 |  | <p>4 Channel Penta-brid DVR (1080P)</p> <ul style="list-style-type: none"> >Penta – brid: Support HDCVI/ HDTVI/ AHD Analog & IP Camera > All Channel @ 1080N Recording, > HDMI & VGA Out Put Up to 1080P > Support 01 HDD (Up to 6 TB) > Full Metal Casing | 3,200.00 |



| | | | | |
|----|--|---|--|----------|
| 02 | XVR1A08 |  | 8 Channel PENTA - BRID DVR (1080N) > Penta – brid: Support HDCVI/ HDTV/ AHD Analog & IP Camera > All Channel @ 1080N Recording > HDMI & VGA Out Put Up to 1080P > Support 01 HDD (Up to 6 TB) > Full Metal Casing | 4,050.00 |
| 03 | XVR1B16-I |  | 16 Channel Penta-brid 1080N/720p Compact 1U 1HDD WizSense Digital Video Recorder > H.265+/H.265 dual-stream video compression > Supports Full-channel AI-Coding > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth > Up to 8 channels video stream (Analog channel) SMD Plus | 7,500.00 |
| 04 | XVR1B04H-I (Up to 5 MP Supported) |  | 4 Channel Penta-brid 5M-N/1080p Cooper 1U 1HDD WizSense Digital Video Recorder (DVR) > H.265+/H.265 dual-stream video compression > Supports Full-channel AI-Coding > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 6 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth, Up to 4 channels video stream (analog channel) SMD Plus, > Support 01 HDD (Up to 6 TB) | 4,950.00 |



| | | | | |
|----|---|---|--|-----------------------------|
| 05 | <p>XVR1B08H-I (Up to 5 MP Supported)</p> |  | <p>8 Channel Penta-brid 5M-N/1080p Cooper 1U 1HDD WizSense Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports Full-channel AI-Coding > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 12 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps incoming bandwidth > Up to 8 channels video stream (analog channel) SMD Plus <ul style="list-style-type: none"> > Support 01 HDD (Up to 6 TB) > Full Metal Casing | 6,300.00 |
| 06 | <p>XVR1B16H (Up to 5 MP Supported)</p> |  | <p>16 Channel Penta-brid 4M-N/1080P Cooper 1U 1HDD Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 24 channels IP camera inputs, each channel up to 6MP; Max 96Mbps incoming bandwidth > Long transmission distance over coax cable > Supports 1 SATA HDD, up to 6TB > Smart Search and Intelligent Video System <ul style="list-style-type: none"> > Full Metal Casing | 9,800.00 Upcoming |


| | | | | |
|----|---------------------|---|--|-----------|
| 07 | XVR4104HS-X1 |  | <p>4 Channel Penta-brid 720P Compact 1U Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 5 channels IP camera inputs, each channel up to 2MP; Max 20Mbps incoming bandwidth > Long transmission distance over coax cable > Supports 1 SATA HDD, up to 6TB | 3,300.00 |
| 08 | XVR4108HS-X1 |  | <p>8 Channel Penta-brid 720P Compact 1U Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 10 channels IP camera inputs, each channel up to 6MP; Max 40Mbps incoming bandwidth > Long transmission distance over coax cable > Supports 1 SATA HDD, up to 6TB | 4,300.00 |
| 09 | XVR4216AN-I |  | <p>16 Channel Penta-brid 720P 1U 2HDDs WizSense Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 video compression > Supports Full-channel AI-Coding > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth > Long transmission distance over coax cable > Up to 8 channels video stream (Analog channel) SMD Plus, > Supports 2 SATA HDD, up to 10 TB | 10,800.00 |

| | | | | |
|----|--|---|--|----------|
| 10 | XVR5104HS-I2 (Up to 5 MP Supported) |  | <p>4 Channel Penta-brid 5M-N/1080P Compact 1U WizSense Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 6 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth > Up to 2 channels video stream (analog channel) Perimeter Protection, Up to 4 channels video stream (analog channel) SMD Plus, Up to 1 channel video stream (analog channel) human face recognition, IoT & POS functionalities, Supports 1 SATA HDD, up to 6TB, Full Metal Casing | 5,300.00 |
| 11 | XVR5108HS-I2 (Up to 5 MP Supported) |  | <p>8 Channel Penta-brid 5M-N/1080P Compact 1U WizSense Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 12 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps incoming bandwidth > Up to 2 channels video stream (analog channel) Perimeter Protection, Up to 8 channels video stream (analog channel) SMD Plus, Up to 2 channels video stream (analog channel) human face recognition, IoT & POS functionalities > Supports 1 SATA HDD, up to 10TB > Full Metal Casing | 6,800.00 |

| | | | | |
|----|--|---|---|-------------------------------|
| 12 | XVR5116HS-I2 (Up to 5 MP Supported) |  | <p>16 Channel Penta-brid 5M-N/1080P Compact 1U 1HDD WizSense Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth > Perimeter Protection and SMD Plus, Up to 2 channels video stream (analog channel) human face recognition, IoT & POS functionalities > Supports 1 SATA HDD, up to 10TB > Full Metal Casing | <p>11,500.00 Upcoming</p> |
| 13 | XVR5216AN-I2 (Up to 5 MP Supported) |  | <p>16 Channel Penta-brid 5M-N/1080P 1U 2HDDs WizSense Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth > Up to 2 channels video stream (analog channel) Perimeter Protection, Up to 16 channels video stream (analog channel) SMD Plus, Up to 2 channels video stream (analog channel) human face recognition > IoT & POS functionalities > Supports 2 SATA HDD, up to 20TB | <p>12,500.00</p> |

| | | | | |
|----|--|---|--|-----------|
| 14 | XVR5232AN-S2 (Up to 5 MP Supported) |  | <p>32 Channel Penta-brid 1080P Digital Video Recorder</p> <ul style="list-style-type: none"> > Embedded processor > H.264+/H.264 dual-stream video compression > Support HDCVI/AHD/TVI/CVBS/IP video inputs > Max 32 channels IP camera inputs; Max 128Mbps Incoming Bandwidth > Long transmission distance over coax cable > Support 2 SATA HDD, up to 16TB | 25,500.00 |
| 15 | XVR5416L-I2 |  | <p>16 Channel Penta-brid 5M-N/1080P 1.5U WizSense Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 24 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth > Up to 2 channels video stream (analog channel) perimeter protection, Up to 16 channels video stream (analog channel) SMD plus, Up to 2 channels video stream (analog channel) human face recognition, IoT & POS functionalities > Internal HDD: 4 SATA Ports, up to 10TB capacity for each dis | 35,500.00 |

| | | | | |
|----|--------------------|---|---|-----------|
| 16 | XVR5432L-I2 |  | <p>32 Channel Penta-brid 5M-N/1080P 1.5U WizSense Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth > Up to 2 channels video stream (analog channel) perimeter protection, Up to 16 channels video stream (analog channel) SMD plus, Up to 2 channels video stream (analog channel) human face recognition, IoT & POS functionalities > Internal HDD: 4 SATA Ports, up to 10TB capacity for each dis | 45,000.00 |
| 17 | XVR5816S-I2 |  | <p>16 Channel Penta-brid 5M-N/1080P 2U WizSense Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 24 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth > Up to 2 channels video stream (analog channel) perimeter protection, Up to 16 channels video stream (analog channel) SMD plus, Up to 2 channels video stream (analog channel) human face recognition > IoT & POS functionalities > Internal HDD: 8 SATA Ports, up to 10TB capacity for each disk | 45,000.00 |

| | | | | |
|----|-------------------|---|---|-----------|
| 18 | XVR5832S-X |  | <p>32 Channel Penta-brid 1080P 2U Digital Video Recorder</p> <ul style="list-style-type: none"> > H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs > Max 32 channels IP camera inputs, each channel up to 8MP; Max 128Mbps incoming bandwidth > First 16 channels support Tripwire & Intrusion; First 2 channels support Object Abandoned & Missing, <p>Supports HDMI2 for spot output</p> <ul style="list-style-type: none"> > Internal HDD: 8 SATA Ports, up to 10TB capacity for each disk | 60,000.00 |
|----|-------------------|---|---|-----------|